
MAVIS update: WFSing and control

Jesse Cranney^{1,2}, Cedric Plantet^{*3}, Guido Agapito³, Olivier Beltramo-Martin⁴, Maria Bergomi⁵, Jean-Claude Bouret⁴, David Brodrick^{1,2}, Giovanni Cresci³, Nicolas Doucet^{1,2}, Damien Gratadour^{1,2,6}, Pierre Haguenaier⁷, Dionne Haynes^{2,1}, Richard Mcdermid^{8,2}, Enrico Pinna³, Kalyan Radhakrishnan Santhakumari⁵, Francois Rigaut^{2,1}, Valentina Viotto⁵, and Hao Zhang^{2,1}

¹Advanced Instrumentation Technology Centre, Research School of Astronomy and Astrophysics,
Australian National University, Canberra – Australia

²Astralis Instrumentation Consortium – Australia

³INAF - Osservatorio Astrofisico di Arcetri – Italy

⁴Laboratoire d'Astrophysique de Marseille – Le Laboratoire D'Astrophysique De Marseille – France

⁵INAF - Osservatorio Astronomico di Padova – Italy

⁶Laboratoire d'études spatiales et d'instrumentation en astrophysique (LESIA) – Observatoire de Paris,
Observatoire de Paris – France

⁷European Southern Observatory – Germany

⁸Australian Astronomical Optics, Macquarie University, Sydney – Australia

Abstract

The MCAO Assisted Visible Imager and Spectrograph (MAVIS) is approaching PDR, and will begin the final design phase in 2023. In order for MAVIS to satisfy the tight error budget for V-band wide-field imaging, novel WFSing and control concepts have been employed. We present a status update on various aspects of the MAVIS WFSing and control design.

*Speaker