



# Demonstration of a photonic-lantern focal-plane wavefront sensor using fibre mode conversion and deep learning

---

Image credit: Velázquez-Benítez+ 2018





THE UNIVERSITY OF  
SYDNEY



# Why?

- Focal-plane WFS directly samples complex E field
  - Minimal NCPA
  - Sensitive to 'blind' modes, e.g. petalometry
  - Measure WF and PSF all at once
- Entire WFS in small, stable, monolithic photonic package
  - Compact, fits in standard fibre connector, easy to implement (incl multi-object)
  - Outputs in standard fibres, easily routable to detector
  - Optimal pixel usage - one pixel per mode (per wavelength...)
- Simple to spectrally disperse (standard fibre slit + grating)
  - Phase unwrapping
  - Scintillation
- Optimal SM fibre injection
  - Multi channel, high-R spectroscopy wants SM fibres
  - Normally it's very hard to inject into SMF!
  - Combine FP-WFS and science fibre(s) into single device
- Complete spectro-imaging and wavefront sensing
  - Like an IFU but
    - Modal, rather than pixel, basis
    - Get complex electric fields for each spatial element - provides WFSing, image reconstruction with optimal speckle suppression






WHAT'S A PHOTONIC  
LANTERN WAVEFRONT  
SENSOR?

WHAT'S A PHOTONIC  
LANTERN? WAVEFRONT  
~~SENSOR?~~

# The photonic lantern

- Photonic device that converts light from a multi-mode to single-mode system and vice-versa with low loss
  - e.g. 1 MMF to multiple SMFs
- Direct relationship between input modes excited and output SMF flux (information preserved -> light preserved)
- Proposed use in astronomy to allow single-mode-spectroscopy despite seeing
- Used in telecommunications in SDM



**A) Multicore fibre to MM fibre (37x1)**

**B) SM fibres to MM fibre (7x1)**

**C) Ultrafast laser inscription (16x1) – bulk glass**

Labels in the diagrams include: MM fiber, Multicore fiber, Fiber bundle, MM fiber, Waveguide array, MM waveguide, Low index jackets, and Bulk glass cladding.


# How do we go “diffraction-limited”?

## Photonic lantern


“It is a photonic device that converts light from a multimode to a single-mode system and vice versa with low loss”

### How do we make them?

Photonics transition to “transform” the MM system into the SM one and vice versa.



## How do they work?




The second law of thermodynamics (brightness theorem) **prohibits the lossless coupling of light from an arbitrarily excited MMF into one SMF HOWEVER** low-loss coupling to another degenerate multimode system with at least as many degrees of freedom is possible.

$$S = k_B \ln M^*$$

$$\text{Low-loss} \rightarrow M_{in} \leq M_{out}$$

$M^*$ =unpredictably or incoherently excited modes



Low-loss when **Entropy (S) is not decreased**




# Linear complex transfer matrix - MM to SM

## Transfer matrix

- Linear in complex amplitudes only
- Can't really know this in real life, only in simulations (shown here)
- In real life, measure intensities
- Output intensities are a non-linear function of input wavefront
- Here, for WFSing,  $n_{\text{outputs}} = n_{\text{modes}}$  (current status)
  - For full imaging, etc., want  $n_{\text{outputs}} = 2 * n_{\text{modes}}$  (under development)



## Example prediction - randomly excited input mode ampls & phase



# Sample PSF in fibre-mode basis

Image the PSF using fibre modes, not pixels, as basis

- Simple step-index fibre modes ~LP modes (Bessel functions)
- More complex in practice (vector modes, remnant core structure)
- Could potentially customise (GRIN, PCF...)

PDF -> modal coefficients is complex overlap integral


- Unlike detector pixels, mapping (complex coupling coeff  $\eta$ ) depends on amplitude & phase

$$\eta = \frac{\int E_1 E_2 dA}{\sqrt{\int |E_1|^2 dA \int |E_2|^2 dA}}$$




- Where  $E_1$  is complex PSF,  $E_2$  is complex fibre mode field

Modes are orthogonal

- LP modes, etc., span image space
- Can construct arbitrary complex image from linear complex combination of modes



# PSF mapping to mode intensity





# Photonic lantern as wavefront sensor

Use fluxes at SM outputs to infer wavefront...

- Modes excited at MM input are a function of complex amplitude of light -> SM outputs are also
- If transfer function is known, can work backwards and predict wavefront
  - Note TF is function of both PL itself and injection into MM region
- Cannot precisely specify transfer function at design / manufacture

Key advantages:



- True focal plane wavefront sensor with instantaneous measurement, without linear approximations
- Optimally feed light to spectrograph with truly zero non-common-path
  - MCF directly on spectrograph in Tiger configuration
- Wavelength information for wavefront sensing! Long sought after, e.g. for atmospheric scintillation
- Scales to multiple astronomical objects in field (MOAO)



# Photonic lantern as wavefront sensor

## The transfer function

- Output fluxes are a *non-linear* function of input wavefront (so not a matrix)
- Since can't specify this transfer function during design, so need to *learn* it after implementation
- Use a deep neural network to learn the transfer function, and then predict unknown wavefronts from output fluxes




# LAB RESULTS

# Laboratory demonstration


## Laboratory setup

- Apply arbitrary wavefronts via SLM, inject PSF into MM region of 19 mode PL
- Also includes back-reflection imaging for alignment and characterisation
- 685 nm (1.2nm bw)



## Training and measurement


- Generate wavefront by drawing (from uniform distribution) random Zernike coefficients for first 10 modes - random combinations probe nonlinearity.
  - Each wavefront on average was  $\pi$  radians P-V
- Apply to SLM and measure PL output fluxes for each
- Acquired  $\sim 60\,000$  measurements (much more than needed).  $\sim 30$  s on modern AO system
- Kept 20% secret for testing performance, trained on other 80%.




# Laboratory results

Reconstruct input wavefront with  $RMS$  error of  $5 \times 10^{-3} \pi$  radians (for  $\pi$  radian input WFs)

Activation	Neurons in first layer	Neurons in final layer	Number of hidden layers	RMS error $\times 10^{-3} \pi$ radians
Non-linear (ReLU)	2000	100	2	<b>5.1</b>
	2000	2000	2	<b>5.1</b>
	2000	100	1	<b>5.9</b>
	200	30	6	<b>6.4</b>
	2000	-	0	<b>7.6</b>
	100	100	3	<b>7.6</b>
	100	-	0	<b>17</b>
Linear	-	-	-	<b>30</b>



Note - color scale on residuals 10 times smaller




# Laboratory results

---


Reconstruct wavefront composed of 19 Zernike terms

Wavefront RMS  $\sim 3$  rad

True WF applied to SLM



Predicted WF from photonic lantern




# Laboratory results

---


Reconstruct wavefront composed of 19 Zernike terms + low wind effect (11 coefficients)

Wavefront RMS  $\sim 3$  rad

True WF applied to SLM



Predicted WF from photonic lantern




# Laboratory results

---


Reconstruct Kolmogorov phase screen, using NN predicting first 19 Zernike terms

Wavefront RMS  $\sim 3$  rad

True WF applied to SLM




Predicted WF from photonic lantern



# Laboratory results

---


Raw multi-wavelength data (analysis in progress)



# Laboratory results

---

Raw multi-wavelength data (analysis in progress)




# SCE<sub>x</sub>AO IMPLEMENTATION

# PL @ SCExAO

Currently 19 core PL, simple to swap to future high-mode-count PLs

- Currently monochromatic (1550nm) on C-red 2; Spectrographic (Y though H) with C-Red 1 end 2022
- Daytime tests - apply known wavefronts to SCExAO DM, evaluate PL-WFS reconstruction accuracy
- On-sky tests - compare reconstructed PSF, and reconstructed WF to PWFS\*
- Todo - close the loop!
























Subaru Coronagraphic Extreme Adaptive Optics  
すばるコロナグラフ極限補償光学装置

# System Overview

Hardware








# PL @ SCExAO

---

Currently 19 core PL, simple to swap to future high-mode-count PLs

- Currently monochromatic (1550nm) on C-red 2; Spectrographic (Y though H) with C-Red 1 end 2022
- Daytime tests - apply known wavefronts to SCExAO DM, evaluate PL-WFS reconstruction accuracy
- On-sky tests - compare reconstructed PSF, and reconstructed WF to PWFS\*
- Todo - close the loop!




# SCExAO daytime tests

---

## Low-order Zernike basis

- Here - first 10 Zernike modes, average of 1.3 radians RMS ( $\sim 5$  rad P-V) wavefront error applied
- Randomly drawn 40,000 training images ( $\sim 1$  minute)
- RMS reconstruction error 0.07 radians




# SCExAO daytime tests

---

## Low-wind-effect modes

- Each pupil quadrant parametrised with tip, tilt, piston
- Average applied WF error 1.7 radians RMS
- RMS reconstruction error 0.1 radians




# SCExAO daytime tests

---

## Petalling-only modes

- Each pupil quadrant parametrised by piston term
- Average applied WF error 2 radians RMS
- RMS reconstruction error 0.09 radians




# SCExAO daytime tests





---

## Petalling-only modes



- Each pupil quadrant parametrised by piston term
- Average applied WF error 2 radians RMS
- RMS reconstruction error 0.09 radians




# SCExAO daytime tests




# SCExAO daytime tests



True image from IRcam (log, clipped)




Predicted image from PL (log, clipped)



# ON SKY RESULTS


# First light of (non-mode selective) time-resolved PL (@ Subaru)



# On sky observations at SCExAO

Here - WF truth data used is first 19 modes from PWFS, as per usual linear basis used in SCExAO


- Prediction is in DM actuator space
- Linear PWFS modes mean won't see LWE, etc. Next step to use optimal modal representation for comparison.



# On sky observations at SCExAO

Here - WF truth data used is first 19 modes from PWFS, as per usual linear basis used in SCExAO

- Prediction is in DM actuator space
- Linear PWFS modes mean won't see LWE, etc. Next step to use optimal modal representation for comparison.




BEYOND WFSING


# On sky PSF reconstructio

## Reconstruct IR PSF using PL


- On-sky IR camera data acquired as well as PL on SCEXAO
- Note PIAA used, so Airy rings suppressed
- NN learns non-linear 'modes' representing aberrations
- Important 'modes' include tip/tilt with corresponding diffraction features due to misalignment with PIAA




True image from IRcam (log)




Predicted image from PL (log)



True image from IRcam (log, clipped)




Predicted image from PL (log, clipped)




# On sky PSF reconstruction

## Reconstruct IR PSF using PL


- On-sky IR camera data acquired as well as PL on SCExAO
- Note PIAA used, so Airy rings suppressed
- NN learns non-linear ‘modes’ representing aberrations
- Important ‘modes’ include tip/tilt with corresponding diffraction features due to misalignment with PIAA




True image from IRcam (log)




Predicted image from PL (log)



True image from IRcam (log, clipped)



Predicted image from PL (log, clipped)






76.000 ms  
Frame 152

# Exploring the model's latent space

---

What “modes” does the model use to represent the PL system?

- “Modes” in quotes since it's non-linear function, not linear combination of 19 modes
- But it's informative to move around the (19-d) input space to see how PL / model describes system with 19 DOF
- Here - pick a PL measurement instance and perturb the PL output intensities






# Exploring the model's latent space

---

What “modes” does the model use to represent the PL system?

- “Modes” in quotes since it's non-linear function, not linear combination of 19 modes
- But it's informative to move around the (19-d) input space to see how PL / model describes system with 19 DOF
- Here - pick a PL measurement instance and perturb the PL output intensities



# OPTIMAL SM INJECTION



# Optimal SMF injection with integrated WFSing

## Implementation

- Introduce anisotropy in preform such that transition to certain mode (LP01 or LP02) has geometric component (not fn of wavelength)
  - LP02 good match to Airy disc, LP01 to apodised PSF
- Optimise AO PSF to excite only e.g. LP01 -> LP01 output fibre to spectrograph
- Light coupled into higher modes (due to WF error) in AO servo loop to keep LP01 maximised
- **Alternatively, do the opposite** - discard the light in LP01 or LP02 and do imaging with remaining fields ->
  - This removes the majority of the starlight from the imaging modes, reducing photon noise (~factor of 10) at the expense of inner-working-angle

## Applications




- Spatially unresolved spectroscopy, e.g. radial velocity
- Long baseline interferometry (each telescope to one fibre, for photonic beam combiner)
- Fibre nulling, such as Vortex Fibre Nuller
- Optimal SNR imaging



# Optimal SMF injection with integrated WFSing



## Implementation

- Introduce anisotropy in preform such that transition to certain mode (LP01 or LP02) has geometric component (not fn of wavelength)
- LP02 good match to Airy disc, LP01 to apodised PSF
- Optimise AO PSF to excite only e.g. LP01 -> LP01 output fibre to spectrograph
- Light coupled into higher modes (due to WF error) in AO servo loop to keep LP01 maximised
- Alternatively, do the opposite - discard the light in LP01 or LP02 and do imaging with remaining fields




# What the PSF looks like with Extreme AO vs fiber mode fields

- All mode fields span ~the same spatial region (the physical fibre core)
- Superposition of modes can describe any image (up to spatial frequency sampled by those modes)
- LP01 biased towards centre. If hybrid mode selective, could remove (or optimal suppress in data analysis) these modes.





# Transfer matrix

- Complex transfer matrix produced by BPM simulations -
  - Excite each input mode (found with FEM) one at a time, calculate complex overlap integral of all output waveguides
- Performance evaluated by mode selectivity of MS waveguide (LP01) to input LP01 mode. <0.1% crosstalk (simulation)
- Devices currently being fabricated for lab tests



# Broadband test (1)



- Input modes excited by randomly selected set of amplitudes ( $0 < A < 1$ ) and phases ( $0 < \phi < \pi$ ).
- Standard outputs show the expected strong, non-linear amplitude modulation as function of wavelength
- Interference between different modes with different propagation constants
- Mode-selective output has constant achromatic amplitude
- Enabled by minimal cross-terms in transfer matrix
- Simulate time series
- Input mode coefficients move in random walk (Gaussian sampling distribution, 0.1 rad / step)
- When used in adaptive optics:
  - Reference set to maximally excite LP01 input mode, and hence maximise output from the MS output, driven by feedback from the WFSing fibers



For optimal injection case - maximise green line by minimising other WFS outputs

# Broadband test (1)

- Input modes excited by randomly selected set of amplitudes ( $0 < A < 1$ ) and phases ( $0 < \phi < \pi$ ).
- Standard outputs show the expected strong, non-linear amplitude modulation as function of wavelength
  - Interference between different modes with different propagation constants
- Mode-selective output has constant achromatic amplitude
  - Enabled by minimal cross-terms in transfer matrix
- Simulate time series
  - Input mode coefficients move in random walk (Gaussian sampling distribution, 0.1 rad / step)
- When used in adaptive optics:
  - Reference set to maximally excite LP01 input mode, and hence maximise output from the MS output, driven by feedback from the WFSing fibers



For optimal injection case - maximise green line by minimising other WFS outputs


# Next step... Complete spectro-imaging and wavefront sensing

## Concept

- Use all the modes for imaging!
- Like IFU, but modes, not pixels
- More optimal than pixels, ranked by spatial frequency
- Output fluxes from SM fibres projected back into image space in data reduction


## Full wave

- Image reconstruction with access to full complex amplitude at focal plane
- Optimal speckle rejection
- >2x as many SM guides as MM modes
- Photon-noise limited, full aperture imaging at  $\sim 0.5\lambda/D$  (interferometric criteria)
- Outputs used for WFS (realtime), spectro-imaging (offline)



# Conclusion

- Adaptive optics limited by current wavefront sensors
  - Non common to science image & blind to some modes
  - Image itself degenerate (not phase information)
- Photonic lantern wavefront-sensor:
  - Senses complex amplitude at image plane
  - Infers input wavefront injected into MM waveguide by measuring SM output fluxes from PL
  - Learns transfer function via neural network
  - Laboratory and on-sky tests show promising results
- PL-WFS allows
  - No NCP aberrations, sensitivity to blind modes
  - Wavelength-dispersed WFSing
  - Also allows reconstruction of PSF!
- Hybrid mode-selective photonic lantern
  - One mode (eg LP01) mapped directly to one output fiber over a broad bandwidth
  - Remaining fibres used for wavefront sensing
  - Ideal for optimal injection into a SMF, with truly zero NCPA and at same wavelength as science



**Next step - complete E field reconstruction for combined imaging + WFSing. Imaging with optimal speckle suppression!**